

Quick Spec Guide

Crestline® Elite Primed Wood French Door (6510, 6610)

SPECIFICATION	STANDARD FEATURES	OPTIONAL FEATURES
EXTERIOR FINISH	<ul style="list-style-type: none"> Primed 	<ul style="list-style-type: none"> Primed with Flat Casing (3-1/2" -6")
EXTERIOR TRIM	<ul style="list-style-type: none"> Standard Brickmould 	<ul style="list-style-type: none"> Stucco Keyed WM 180 Historical Stucco Keyed Historical
INTERIOR FINISH	<ul style="list-style-type: none"> Natural 	<ul style="list-style-type: none"> Clear Satin Fruitwood Primed Golden Oak Chestnut Prefinished White
INTERIOR SPECIES	<ul style="list-style-type: none"> Pine 	<ul style="list-style-type: none"> Oak Maple Alder (Character) Cherry Mahogany Vertical Grain Fir
SIZE	<ul style="list-style-type: none"> Width Single Panel Doors 2-1, 2-7, 2-9, 3-1 Two Panel Doors 4-0, 5-0, 5-4, 6-0 Height Single and Two panel Doors 6-8, 6-10, 7-2, 8-0, 9-0, 10-0 	<ul style="list-style-type: none"> Single Panel Side Hinged Doors: Any jamb width: 24-5/16" to 36-5/16" Two Panel Side Hinged Doors: Any jamb width: 47-1/4" to 71-1/4" Single Panel and Two Panel Side Hinged Doors: Any jamb height: 79-1/2" to 120"
GLAZING	<ul style="list-style-type: none"> Clear Insulated Glass Tempered Glass Warm Edge Spacer System Free Accidental Glass Breakage Warranty 	<ul style="list-style-type: none"> Low E Low E Sun240 Zo-E Shield 5 Zo-E Shield 5E Zo-E Shield 6 (laminated) SafeGuard Certified Gray or Bronze Tint Obscure
GRILLES		<ul style="list-style-type: none"> GIA: 5/8" Flat or 3/4" Profiled SDL: 7/8", 1-3/8" Wood Grille: 7/8", 1-3/8"
HARDWARE	<ul style="list-style-type: none"> Multi-Point Lock Arched Plate Keyed lock Adjustable hinge Manual Flush Bolt w/ Dummy Handles 	<ul style="list-style-type: none"> 2 Bore (5-1/2" OC) No Bore No Lock Prep Square Plate Keyed Alike Lock Lever Activated Inactive Panel
HARDWARE COLOR	<ul style="list-style-type: none"> Bright Brass PVD (handle) Bright Brass (hinge) 	<ul style="list-style-type: none"> Antique Brass Black Brushed Nickel (PVD) (handle) Brushed Nickel (hinge) Chrome Oil Rubbed Bronze Stainless Steel (hinge)
JAMB	<ul style="list-style-type: none"> 4-9/16" 	<ul style="list-style-type: none"> 4-9/16 Min 7-1/8" (inswing), 12" (outswing) Max
HINGING	<ul style="list-style-type: none"> Inswing (6510) 	<ul style="list-style-type: none"> Outswing (6610)
RAILS	<ul style="list-style-type: none"> 5" (top) 7-1/2" (bottom) 	<ul style="list-style-type: none"> 10" (bottom) 12" (bottom)
SILLS	<ul style="list-style-type: none"> Standard 	<ul style="list-style-type: none"> ADA Optional 2" Sill (outswing)